



ART. 3000/55

(kg. 1.20)

- COLONNINA 2 RUBINETTI - DISTRIBUZIONE A Y
- STANDOUT 2 TAPS - Y-DISTRIBUTION
- STANDSÄULE 2 NADELVENTILE - Y-VERTEILER
- COLONNETTE 2 ROBINETS - Y-DISTRIBUTEUR

Body Width 180mm

3000/55 Tap - Standout 2 Taps Y Distribution

www.parslab.com

The 3000/55 Compressed air tap is manufactured to the highest standards using the very latest in robotic engineering, This range of taps has continuously evolved over the last 65 years. Now the tap is manufactured to withstand rigorous use in the most demanding applications. The high quality brass body (P-Cu Zn40 Pb2 UNI 5705-65 Certifications) is Epoxy coated to RAL7001 as standard (light grey) although other colours are available as a special order.

Connection: G3/8 and G1/2 UNI ISO 228/1

Nozzle: Olive-type fixed coupling DIN 12898

With normal regulation. Maintenance free.

Copper pipes available for fume cupboard valves

Maximum working pressure: 10 Bar

Contamination Class 4

Connection: G3/8 and G1/2 UNI ISO 228/1

Nozzle: Olive-type fixed DIN 12898

Upper part: with fine regulation, maintenance free

Copper pipes available for fume cupboard valves

Maximum working pressure: 10 Bar

www.parslab.com